


## Mounting bracket and dowel



### Application


The mounting bracket and dowel are used in any application where the extrusions are subjected to torsion but must not twist. A safe extrusion connection.

### Specification

Aluminium, matt, anodised in natural colours



## Clamping block Base 50/40/30



### Application

To connect two extrusions of base 30, 40 or 50 in parallel or crossing. Two blocks are required to create a parallel connection.

### Specification

Aluminium anodised  
Screw: Zinc-coated steel

### Parts supplied

1/2 clamping block(s), screws



### Measurement data

	A	B	C	E	F	H	L	Ø	t	ø	
Base 30	15	17	20	6.5	2.1	10.6	50	10	5	5.5	M5
Base 40	22	25	25	10	4	15.6	60	11	6.8	6.6	M6
Base 50	27	25	25	10	4	20.6	70	11	6.8	6.6	M6

### Measurement data Order number

B	Ø	M	Order number
30	9	-	A30-13
20	6.5	-	B30-13
30	9	M6	A30-23
20	6.5	M6	B30-23

### Order data

**Extrusion base**  
**Single clamping blocks**  
Cross connection  
Parallel connection  
**Double clamping blocks**  
Cross connection  
Parallel connection

### Order number

50	40	30
A34-01	C34-01	B34-01
A34-11	C34-11	B34-11
A34-02	C34-02	B34-02
A34-22	C34-22	B34-22